

TECHNICAL FEATURES

	Engine	Fuel	Starter	Power kW/hp	Gearbox	Speeds FWD+REV	Quick reverser	Clutch	Brake	Differential	PTO	Handlebar	Wheels	Safety devices	BCS attachments which can be mounted
728 PowerSafe®	HONDA GP160	Gasoline	Recoil	3,6 / 4,8	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Parking brake	No	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height, sideways and reversible	4.00-8 4.0-10 5.0-10 5.0-12 6.5/80-12 Steel cage wheels Ø43 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, cutter bar, lawn mower, BladeRunner, snow blade and turbine snow thrower, sweeper
	HONDA GX200	Gasoline	Recoil	4,1 / 5,5											
	HONDA GX270	Gasoline	Recoil	6,3 / 8,6											
	BRIGGS&STRATTON XR1450	Gasoline	Recoil	7 / 9,5											
	KOHLER KD350	Diesel	Recoil	5,5 / 7,5											
738 PowerSafe®	HONDA GX270	Gasoline	Recoil or electric	6,3 / 8,6	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Parking brake on the two wheels	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height, sideways and reversible	5.0-10 5.0-12 6.5/80-12 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, mulching machine, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	BRIGGS&STRATTON XR1450	Gasoline	Recoil	7 / 9,5											
	HONDA GX340	Gasoline	Recoil	8 / 10,7											
	KOHLER KD350	Diesel	Recoil or electric	5,5 / 7,5											
740 PowerSafe®	BRIGGS&STRATTON XR2100	Gasoline	Recoil	8,4 / 11,5	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Independent working brakes on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height, sideways and reversible	5.0-10 5.0-12 6.5/80-12 6.5/80-15 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, mulching machine, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7											
	YANMAR L100V	Diesel	Recoil or electric	6,8 / 9,1											
750 PowerSafe®	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	3 + 3	Yes	PowerSafe®, hydraulic with manual control	Independent working brakes on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height, sideways and reversible	6.5/80-12 6.5/80-15 Steel cage wheels Ø 58 cm	In compliance with the EN 709/A4 standard	Rotary hoe, ridger, plough, mulching machine, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, sweeper
	KOHLER KD440	Diesel	Recoil or electric	8 / 10,5											
770HY PowerSafe®	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	2-speed ranges (slow/fast) in both FWD and REV	By hydrostatic unit	PowerSafe®, hydraulic with manual control	Independent working brakes on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height, sideways and reversible	5.0-10 5.0-12 6.5/80-12 6.5/80-15 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, mulching machine, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	YANMAR L100V	Diesel	Recoil or electric	6,8 / 9,1											
780HY STARGATE	HONDA GX390	Gasoline	Recoil or electric	8,7 / 11,7	With gears and worm screw in oil bath	One-speed range in both FWD and REV	By hydrostatic unit	PowerSafe®, hydraulic with manual control	Independent working brakes on the two wheels and parking brake	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height, sideways and reversible	5.0-10 5.0-12 6.5/80-12 6.5/80-15 Steel cage wheels Ø 49 cm	In compliance with the EN 709/A4 standard	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, mulching machine, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper
	YANMAR L100V	Diesel	Recoil or electric	6,8 / 9,1											