

TECHNICAL FEATURES

720
Action

Engine	Fuel	Starter	Power kW/HP	Gearbox	Speeds FWD + REV	Quick reverser	Clutch	Brakes	Differential	PTO	Handlebar	Wheels	Safety devices	BCS attachments which can be mounted
HONDA GX200	Gasoline	Recoil	4.1 / 5.5	With gears and worm screw in oil bath	3 + 2 (two-wheel tractor position) 2 + 2 (motor mower position)	Yes	Self-ventilating dry clutch, with manual control	No	No	Independent from gearbox. At 990 rpm (with engine at 3600 rpm with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	4.00-8 4.0-10 6.5/80-12 Steel cage wheels Ø 43 cm	Engine Stop combined with clutch and contrast reverse speed	Rotary hoe, PDR, ridger, plough, cutter bar, lawn mower, BladeRunner, snow blade and turbine snow thrower, sweeper, towed trailer
HONDA GX270	Gasoline	Recoil	6.3 / 8.6											
BRIGGS&STRATTON XR1450	Gasoline	Recoil	7 / 9.5											
KOHLER KD350	Diesel	Recoil	5.5 / 7.5											

730
Action

HONDA GX270	Gasoline	Recoil	6.3 / 8.6	With gears and worm screw in oil bath	3 + 2 (two-wheel tractor position) 2 + 2 (motor mower position)	Yes	Self-ventilating dry clutch, with manual control	No	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	Engine Stop combined with clutch and contrast reverse speed	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper, towed trailer
HONDA GX340	Gasoline	Recoil	8 / 10.7											
BRIGGS&STRATTON XR1450	Gasoline	Recoil	7 / 9.5											
KOHLER KD350	Diesel	Recoil or electric	5.5 / 7.5											

740
Action

HONDA GX390	Gasoline	Recoil or electric	8.7 / 11.7	With gears and worm screw in oil bath	4 + 3 (two-wheel tractor position) 3 + 3 (motor mower position)	Yes	Self-ventilating dry clutch, with manual control	Independent working brakes on the two wheels	With lock	Independent from gearbox. At 990 rpm (with engine at 3600 rpm) with engagement in oil bath	Mounted on silent-blocks, adjustable in height and sideways and reversible	5.0-10 6.5/80-12 Steel cage wheels Ø 49 cm	Engine Stop combined with clutch and contrast reverse speed	Rotary hoe, PDR, ridger, plough, GroundBlaster, Ridge 2, cutter bar, lawn mower, heavy-duty mower, BladeRunner, RollerBlade, snow blade and turbine snow thrower, sweeper, towed trailer, work and travel sulky
BRIGGS&STRATTON XR2100	Gasoline	Recoil	8.4 / 11.5											
YANMAR L100V	Diesel	Recoil or electric	6.8 / 9.1											
KOHLER KD440	Diesel	Recoil or electric	8 / 10.5											

For more info, size and weights go to www.bcsagri.com