

ROTEX XT

REAR-MOUNTED DISC MOWERS

TECHNICAL FEATURES	ROTEX XT 4	ROTEX XT 5	ROTEX XT 6	ROTEX XT 7
Number of discs	4	5	6	7
Cutting width (mm)	1650	2050	2450	2850
Min/max swath width (mm)	250 / 650	650 / 1050	1050 / 1450	1450 / 1850
Weight (kg)	520	560	600	645
Power required at PTO (kW/hp)	20 / 27	25 / 34	30 / 41	35 / 48
Chassis with cat. 2 and 3 hitches	standard			
Tractor PTO rotation speed	540 rpm			
Spheroidal cast iron gearbox	standard			
Transmission	with gears in oil bath			
Disc rotation	counter-rotating	normal or counter-rotating		
Disc flanges with torque limiter	standard			
Conveyor cones	positioned on the first and last discs as standard			
Adjustable swath boards	standard, of which external swath wheel			
Wear-resistant special boron/ manganese steel skids	standard			
Baffles situated in the blade overlap zones	standard			
Safety release with retraction of the bar in the event of impact against obstacles	standard			
Bar balancing by means of lightening springs and tie rods	standard			
Bar protection	in synthetic fabric	made of synthetic fabric with protective plastic impact shields		
Hydraulic cutter bar lift	standard			
Hydraulic distributors required on the tractor	1 single acting			
Bar inclination	from +90° (transport position) to -35° in relation to the horizontal plane			
Cardan shaft with free release	standard			