

ROTEX EDELWEISS

FRONT-MOUNTED DISC MOWERS

TECHNICAL FEATURES	ROTEX EDELWEISS AS5	ROTEX EDELWEISS AS6	ROTEX EDELWEISS AS7
Number of discs	5	6	7
Cutting width (mm)	2050	2450	2850
Max. width in working condition (mm)	2700	3100	3500
Max. width in transport condition (mm)	2050	2450	2850
Swath width (mm)	1480	1880	2280
Weight without hitch (kg)	380	420	460
Weight with Standard hitch (kg)	450	490	530
Power required at PTO (kW/hp)	30 / 40	35 / 48	40 / 54

Tractor attachment frame	3-point category 1 and 2, available in different versions for hitching to all tractor types
Hydraulic displacement	available as an option (requires 1 double-acting distributor), allows transverse movement of approximately 175 mm on both sides
Bar lightening	via hydraulic tractor suspension, spring relief kit for conventional tractors available as an option
Drive box	prepared for both clockwise and anti-clockwise PTO tractors
Gearbox	light alloy, gears in oil bath with torque limiting clutch
Drive unit	with integrated free release
Central joint	with +/- 4° tilting and lockable during transport
Cutter bar	with transmission with gears in oil bath
Disc rotation	counter-rotating
Disc holder flanges	with torque limiter
Bar protection	baffles situated in the blade overlap zones
Conveyor cones	positioned on the first and last discs as standard
Swath boards	non-adjustable
Slides	wear-resistant special boron/manganese steel
Cutting unit protection	synthetic tarpaulin front and top
Side guards	reclining for road transport